



DATA SHEET

PYROGUARD RAPIDE EW30

PYROGUARD RAPIDE EW30 IMPACT, 7MM is perfect for indoor and outdoor use. It's large sheet size and double sided fire resistance can be cut to size making it a cost effective solution.

TECHNICAL INFORMATION

Fire Resistance (EN 13501-2)	EW30
Impact Resistance (EN 12600)	2(B)2
Light Transmission	90%
Sound reduction	33 dB
U Value	5.7 W/m ² K
UV Stability (EN ISO 12543-4)	Yes
Nominal Thickness	7 mm
Thickness Tolerance	-0.6 / +0.8 mm
Weight	17 kg per m ²
Temperature Range	-20 / +100 °C
Sheet Size	1580 x 2780 mm


KEY FEATURES


- ☒ EW30 Impact
- ☒ 2(B)2 impact classification
- ☒ Interior and exterior use
- ☒ Double sided fire resistance
- ☒ UV stability
- ☒ Steel & timber applications

SUITABLE APPLICATION

- ☒ Can be used in fire tested timber and steel systems.

STORAGE AND HANDLING

-  Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

-  If you need help, please email: technical@fireglassuk.com

-  CERTIFIRE REF: CF257



FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: TECHNICAL@FIREGLASSUK.COM

ACCREDITATION & CERTIFICATION

