



## DATA SHEET

# PYROGUARD RAPIDE EW30 MAXI

**PYROGUARD RAPIDE EW30 MAXI, 11MM** is perfect for indoor and outdoor use. It's large sheet size and double sided fire resistance can be cut to size making it a cost effective solution.

## TECHNICAL INFORMATION

Fire Resistance (En 13501-2)	EW30
Impact Resistance (EN 12600)	2(B)2
Light Transmission	88%
Sound reduction	35 dB
U Value	5.5 W/m <sup>2</sup> K
UV Stability (EN ISO 12543-4)	Yes
Nominal Thickness	11mm
Thickness Tolerance	-1 / +1.4 mm
Weight	27 kg per m <sup>2</sup>
Temperature Range	-20 / +100 °C
Sheet Size	1580 x 2780 mm


## KEY FEATURES


- ☒ EW30 Impact
- ☒ 2(B)2 impact classification
- ☒ Interior and exterior use
- ☒ Double sided fire resistance
- ☒ UV stability
- ☒ Steel & timber applications

## SUITABLE APPLICATION

- ☒ Can be used in fire tested timber, steel and aluminium systems.

## STORAGE AND HANDLING

-  Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

 If you need help, please email: [technical@fireglassuk.com](mailto:technical@fireglassuk.com)

 CERTIFIRE REF: CF257



**FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.**

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: [TECHNICAL@FIREGLASSUK.COM](mailto:TECHNICAL@FIREGLASSUK.COM)

## ACCREDITATION & CERTIFICATION

